

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

### Listing of Claims

1 Claim 1 (Currently Amended): A method of setting up a plurality of virtual circuits  
2 between a first end system and a second end system, said plurality of virtual circuits being  
3 set up on a network connecting said first end system to said second end system, each of  
4 said plurality of virtual circuits terminating at said first end system and said second end  
5 system, said method being performed in a device between said first end system and said  
6 second end system, said method comprising:

7 sending to said second end system a first signaling message requesting said plurality  
8 of virtual circuits to be set up;

9 receiving an acceptance message, said acceptance message indicating that a  
10 plurality of switches in a connection path between said first end system and said second  
11 end system have set up said plurality of virtual circuits, wherein said plurality of switches  
12 accept said plurality of virtual circuits but immediately provision fewer than said plurality  
13 of virtual circuits; and

14 \_\_\_\_\_ sending a second signaling message to activate at least one of a plurality of not-yet-  
15 provisioned virtual circuits comprised in said plurality of virtual circuits.

1 Claim 2 (Original): The method of claim 1, wherein said first signaling message  
2 comprises a plurality of information elements, wherein a first information element is  
3 designed to request set up of a single virtual circuit comprised in said plurality of virtual  
4 circuits, and a second information element is designed to request set up of a second  
5 plurality of virtual circuits comprised in said plurality of virtual circuits, further  
6 comprising:

7 receiving an acceptance message indicating that only said single virtual circuit is  
8 possible to be provisioned if any of a plurality of switches in a connection path between  
9 said first end system and said second end system is designed not to support said plurality  
10 of virtual circuits.

1 Claim 3 (Original): The method of claim 2, wherein said second information  
2 element comprises a non-mandatory information element according to a specification,

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

3 wherein non-mandatory information elements can be ignored by said plurality of switches  
4 according to said specification.

1 Claim 4 (Original): The method of claim 3, wherein said specification comprises  
2 one of user to network interface (UNI) and network to network interface (NNI).

1 Claim 5-6 (Canceled)

2 Claim 7 (Currently Amended): The method of claim 1 6, wherein said fewer than  
3 said plurality of virtual circuits corresponds to one virtual circuit such that only one virtual  
4 circuit is provisioned in response to said first signaling message.

1 Claim 8 (Currently Amended): The method of claim 1 5, wherein said plurality of  
2 virtual circuits is treated as a group of virtual circuits, wherein said first end system and  
3 said second end system support a plurality of groups including said group, said method  
4 further comprising maintaining a bundle structure associated with each of said plurality  
5 of groups, wherein said bundle structure stores information identifying the specific  
6 plurality of virtual circuits forming the corresponding group.

1 Claim 9 (Original): The method of claim 8, further comprising:  
2 maintaining a plurality of call reference structures, wherein each of said plurality  
3 of call reference structures maintains the state of a call, wherein signaling messages related  
4 to each group are received on a corresponding call; and  
5 maintaining a plurality of per-VC structures, wherein each per-VC structure stores  
6 information related to a plurality of call parameters accepted for a corresponding one of  
7 said plurality of virtual circuits.

1 Claim 10 (Original): The method of claim 9, wherein said sending, said receiving  
2 and each of said maintaining are performed in a switch contained in said connection path,  
3 said method further comprising:

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

4 maintaining a plurality of switch structures, wherein each of said plurality of switch  
5 structures stores a mapping of an identifier of each of said virtual circuit in inbound  
6 direction to another identifier of the virtual circuit in outbound direction;  
7 mapping each identifier received in inbound direction to a corresponding identifier  
8 in outbound direction using said plurality of switch structures.

1 Claim 11 (Original): The method of claim 9, wherein said first end system  
2 comprises an edge router and wherein said method is performed in said first edge router,  
3 wherein said first signaling message contains a bundle identifier which is propagated  
4 without translation by each of said plurality of switches.

1 Claim 12 (Original): The method of claim 11, wherein each of said plurality of  
2 virtual circuits comprises a switched virtual circuit.

1 Claim 13 (Currently Amended): The method of claim 1-6, wherein said acceptance  
2 message and said first signaling message are both formed according to a common format,  
3 wherein said common format contains a field which indicates whether a message  
4 comprises said acceptance message or said first signaling message.

1 Claim 14 (Original): The method of claim 13, wherein said format allows a range  
2 of virtual circuits to be specified, said format further allowing a plurality of traffic  
3 parameters to be specified for all of said range of virtual circuits, wherein said plurality  
4 of parameters in said first signaling message specify the desired parameters and said  
5 plurality of parameters in said acceptance message specify the accepted parameters.

1 Claim 15 (Original): The method of claim 14, further comprising sending a release  
2 message requesting release of another range of virtual circuits.

1 Claim 16 (Currently Amended): A method of supporting the setting up of a plurality  
2 of virtual circuits between a first end system and a second end system, said plurality of

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

virtual circuits being set up on a network connecting said first end system to said second end system, each of said plurality of virtual circuits terminating at said first end system and said second end system, said method being performed in a device, said method comprising:

receiving from said first end system a first signaling request requesting said plurality of virtual circuits to be set up;

provisioning fewer than said plurality of virtual circuits to said second end system;

sending an acceptance message if said plurality of virtual circuits can be set up between said device and said second end system in response to said first signaling request alone, wherein said sending is performed after said provisioning;

receiving a second signaling message requesting activation of at least one of said not-yet-provisioned virtual circuits comprised in said plurality of virtual circuits;

completing provisioning of said at least one of said not-yet-provisioned virtual circuits; and

sending a completion message indicating said at least one of said not-yet-provisioned virtual circuits have been activated.

Claims 17-20 (Canceled)

Claim 21 (Currently Amended): The method of claim ~~16~~ 20, wherein said first signaling ~~message request~~ contains a plurality of parameters related to a range of virtual circuits comprised in said plurality of virtual circuits, said method further comprising:

storing said plurality of parameters associated with said range of virtual circuits;

and

provisioning said range of virtual circuits using said plurality of parameters,

whereby said plurality of parameters are transmitted only once for provisioning said range of virtual circuits.

Claim 22 (Original): The method of claim 21, wherein said first signaling request and said second signaling message are received in the form of ATM cells.

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

1 Claim 23 (Original): The method of claim 22, wherein said device comprises one  
2 of said first end system, said second end system and a switch in the path of said plurality  
3 of virtual circuits connecting said first end system to said second end system.

1 Claim 24 (Original): A device for setting up a plurality of virtual circuits between  
2 a first end system and a second end system, said plurality of virtual circuits being set up  
3 on a network connecting said first end system to said second end system, said device  
4 comprising:

5 an outbound interface coupled to said network;  
6 a message construction block coupled to said outbound interface; and  
7 a call control logic for causing said message construction block to construct a first  
8 signaling message requesting said plurality of virtual circuits to be set up, and to send said  
9 first signaling message on said network to said second end system.

1 Claim 25 (Original): The device of claim 24, further comprising a signaling  
2 application programming interface (API), said signaling API receiving a request for a  
3 group of virtual circuits from an external application, and communicating said request to  
4 said call control logic, wherein said call control logic causes said first signaling message  
5 to be sent in response to said request.

1 Claim 26 (Original): The device of claim 25, wherein said outbound interface sends  
2 said first signaling message in the form of a plurality of asynchronous transfer mode  
3 (ATM) cells, said device further comprising:

4 a signaling ATM adaptation layer (SAAL) output block to encapsulate data  
5 generated by said message construction block to generate said first signaling message, said  
6 SAAL output block being coupled to said outbound interface.

1 Claim 27 (Currently Amended): The device of claim 24, wherein said first signaling  
2 message comprises a plurality of information elements, wherein a first information element  
3 is designed to request set up of a single virtual circuit comprised in said plurality of virtual

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

circuits, and a second information element is designed to request set up of a second plurality of virtual circuits comprised in said plurality of virtual circuits, said device further comprising:

an inbound interface designed for receiving on said network an acceptance message indicating that only said single virtual circuit is possible to be provisioned if any of a plurality of switches in a connection path between said first end system and said second end system is designed not to support said plurality of virtual circuits; and

a parser designed for examining said acceptance message and forwarding said acceptance message to said call control logic.

Claim 28 (Original): The device of claim 27, wherein said second information element comprises a non-mandatory information element according to a specification, wherein non-mandatory information elements can be ignored by said plurality of switches according to said specification.

Claim 29 (Original): The device of claim 28, wherein said specification comprises one of user to network interface (UNI) and network to network interface (NNI).

Claim 30 (Currently Amended): The device of claim 24, further comprising an inbound interface designed for receiving an acceptance message, said acceptance message indicating that a plurality of switches in a connection path between said first end system and said second end system have set up said plurality of virtual circuits.

Claim 31 (Currently Amended): The device of claim 30, wherein said plurality of switches accept said plurality of virtual circuits but immediately provision fewer than said plurality of virtual circuits, wherein said call control logic designed for causing causes said message construction block to send a second signaling message to activate at least one of a plurality of not-yet-provisioned virtual circuits comprised in said plurality of virtual circuits.

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

1 Claim 32 (Currently Amended): The device of claim 30, wherein said plurality of  
2 virtual circuits is treated as a group of virtual circuits, wherein said first end system and  
3 said second end system support a plurality of groups including said group, said device  
4 further comprising a memory designed for storing a bundle structure associated with each  
5 of said plurality of groups, wherein said bundle structure stores information identifying the  
6 specific plurality of virtual circuits forming the corresponding group.

1 Claim 33 (Currently Amended): The device of claim 32, wherein said memory is  
2 designed to further stores store a plurality of call reference structures and a plurality of  
3 per-VC structures,

4 wherein each of said plurality of call reference structures maintains the state of a  
5 call, wherein signaling messages related to each group are received on a corresponding  
6 call, and

7 wherein each per-VC structure stores information related to a plurality of call  
8 parameters accepted for a corresponding one of said plurality of virtual circuits.

1 Claim 34 (Currently Amended): The device of claim 33, wherein said device  
2 comprises a switch in said connection path, said memory is further designed for storing  
3 a plurality of switch structures, wherein each of said plurality of switch structures stores  
4 a mapping of an identifier of each of said virtual circuit in inbound direction to another  
5 identifier of the virtual circuit in outbound direction.

1 Claim 35 (Original): The device of claim 33, wherein said first end system  
2 comprises an edge router, wherein said first signaling message contains a bundle identifier  
3 which is propagated without translation by each of said plurality of switches.

1 Claim 36 (Original): The device of claim 30, wherein said acceptance message and  
2 said first signaling message are both formed according to a common format, wherein said  
3 common format contains a field which indicates whether a message comprises said  
4 acceptance message or said first signaling message.

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

1 Claim 37 (Original): The device of claim 36, wherein said format allows a range  
2 of virtual circuits to be specified, said format further allowing a plurality of traffic  
3 parameters to be specified for all of said range of virtual circuits, wherein said plurality  
4 of parameters in said first signaling message specify the desired parameters and said  
5 plurality of parameters in said acceptance message specify the accepted parameters.

1 Claim 38 (Currently Amended): An apparatus for supporting the setting up of a  
2 plurality of virtual circuits between a first end system and a second end system, said  
3 plurality of virtual circuits being set up on a network connecting said first end system to  
4 said second end system, said plurality of virtual circuits terminating at said first end system  
5 and said second end system, said apparatus being contained in a device, said apparatus  
6 comprising:

7 an in-bound interface receiving from said first end system a first signaling request  
8 requesting said plurality of virtual circuits to be set up; and  
9 a call control logic receiving said first signaling message, said call control logic  
10 sending an acceptance message if said plurality of virtual circuits can be set up between  
11 said device and said second end system in response to said first signaling request alone,  
12 wherein said call control logic provisions fewer than said plurality of virtual circuits to said  
13 second end system before sending said acceptance message,  
14 wherein said inbound interface receives a second signaling message requesting  
15 activation of at least one of said not-yet-provisioned virtual circuits comprised in said  
16 plurality of virtual circuits, and  
17 wherein said call control logic completes provisioning of said at least one of said  
18 not-yet-provisioned virtual circuits and then sends a completion message indicating said  
19 at least one of said not-yet-provisioned virtual circuits have been activated.

1 Claims 39 - 42 (Canceled)



Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

1 Claim 43 (Currently Amended): The apparatus of claim 38-42, wherein said first  
2 signaling message contains a plurality of parameters related to a range of virtual circuits  
3 comprised in said plurality of virtual circuits, said apparatus further comprising a memory  
4 storing said plurality of parameters associated with said range of virtual circuits, wherein  
5 said call control logic ~~550~~ provisions said range of virtual circuits using said plurality of  
6 parameters, whereby said plurality of parameters are transmitted only once for  
7 provisioning said range of virtual circuits.

1 Claim 44 (Currently Amended): The apparatus of claim 43, wherein said device  
2 comprises one of said first end system, said second end system and a switch in the path of  
3 said plurality of virtual circuits connecting said first end system to said second end system.

1 Claims 45-52 (Canceled)

2 Claim 53 (Currently Amended): A device for supporting the setting up of a plurality  
3 of virtual circuits between a first end system and a second end system, said plurality of  
4 virtual circuits being set up on a network connecting said first end system to said second  
5 end system, each of said plurality of virtual circuits terminating at said first end system and  
6 said second end system, said device comprising:

7 means for receiving from said first end system a first signaling request requesting  
8 said plurality of virtual circuits to be set up;

9 means for provisioning fewer than said plurality of virtual circuits to said second  
10 end system;

11 means for sending an acceptance message after said provisioning if said plurality  
12 of virtual circuits can be set up between said device and said second end system in  
13 response to said first signaling request alone;

14 means for receiving a second signaling message requesting activation of at least one  
15 of said not-yet-provisioned virtual circuits comprised in said plurality of virtual circuits;

16 means for completing provisioning of said at least one of said not-yet-provisioned  
17 virtual circuits; and

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

18 means for sending a completion message indicating said at least one of said not-yet-  
19 provisioned virtual circuits have been activated.

1 Claims 54 - 57 (Canceled)

1 Claim 58 (Currently Amended): The device of claim 53-57, wherein said first  
2 signaling message contains a plurality of parameters related to a range of virtual circuits  
3 comprised in said plurality of virtual circuits, said device further comprising:

4 means for storing said plurality of parameters associated with said range of virtual  
5 circuits; and

6 means of provisioning said range of virtual circuits using said plurality of  
7 parameters,

8 whereby said plurality of parameters are transmitted only once for provisioning said  
9 range of virtual circuits.

1 Claim 59 (Currently Amended): A computer readable medium carrying one or more  
2 sequences of instructions for causing a device to set up a plurality of virtual circuits  
3 between a first end system and a second end system, said plurality of virtual circuits being  
4 set up on a network connecting said first end system to said second end system, each of  
5 said plurality of virtual circuits terminating at said first end system and said second end  
6 system, said device being located in a communication path located between said first end  
7 system and said second end system, wherein execution of said one or more sequences of  
8 instructions by one or more processors contained in said device causes said one or more  
9 processors to perform the action of:

10 sending to said second end system a first signaling message requesting said plurality  
11 of virtual circuits to be set up;

12 receiving an acceptance message, said acceptance message indicating that a  
13 plurality of switches in a connection path between said first end system and said second  
14 end system have set up said plurality of virtual circuits, wherein said plurality of switches  
15 accept said plurality of virtual circuits but immediately provision fewer than said plurality

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

16 of virtual circuits, wherein said fewer than said plurality of virtual circuits corresponds to  
17 one virtual circuit such that only one virtual circuit is provisioned in response to said first  
signaling message.; and  
sending a second signaling message to activate at least one of a plurality of not-yet-  
1 provisioned virtual circuits comprised in said plurality of virtual circuits.

2 Claim 60 (Original): The computer readable medium of claim 59, wherein said first  
3 signaling message comprises a plurality of information elements, wherein a first  
4 information element is designed to request set up of a single virtual circuit comprised in  
5 said plurality of virtual circuits, and a second information element is designed to request  
6 set up of a second plurality of virtual circuits comprised in said plurality of virtual circuits,  
7 further comprising:  
8 receiving an acceptance message indicating that only said single virtual circuit is  
9 possible to be provisioned if any of a plurality of switches in a connection path between  
10 said first end system and said second end system is designed not to support said plurality  
11 of virtual circuits.

1 Claim 61 (Original): The computer readable medium of claim 60, wherein said  
2 second information element comprises a non-mandatory information element according  
3 to a specification, wherein non-mandatory information elements can be ignored by said  
4 plurality of switches according to said specification.

1 Claim 62-64 (Canceled)

1 Claim 65 (Original): The computer readable medium of claim ~~59~~ 64, wherein said  
2 plurality of virtual circuits is treated as a group of virtual circuits, wherein said first end  
3 system and said second end system support a plurality of groups including said group,  
4 further comprising maintaining a bundle structure associated with each of said plurality  
5 of groups, wherein said bundle structure stores information identifying the specific  
6 plurality of virtual circuits forming the corresponding group.

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

1 Claim 66 (Original): The computer readable medium of claim 65, further  
2 comprising:

3 maintaining a plurality of call reference structures, wherein each of said plurality  
4 of call reference structures maintains the state of a call, wherein signaling messages related  
5 to each group are received on a corresponding call; and

6 maintaining a plurality of per-VC structures, wherein each per-VC structure stores  
7 information related to a plurality of call parameters accepted for a corresponding one of  
8 said plurality of virtual circuits.

1 Claim 67 (Original): The computer readable medium of claim 66, wherein said  
2 sending, said receiving and each of said maintaining are performed in a switch contained  
3 in said connection path, further comprising:

4 maintaining a plurality of switch structures, wherein each of said plurality of switch  
5 structures stores a mapping of an identifier of each of said virtual circuit in inbound  
6 direction to another identifier of the virtual circuit in outbound direction;

7 mapping each identifier received in inbound direction to a corresponding identifier  
8 in outbound direction using said plurality of switch structures.

1 Claim 68 (Original): The computer readable medium of claim 66, wherein said first  
2 end system comprises an edge router and wherein said actions are performed in said first  
3 edge router, wherein said first signaling message contains a bundle identifier which is  
4 propagated without translation by each of said plurality of switches.

1 Claim 69 (Currently Amended): The computer readable medium of claim 59-62,  
2 wherein said acceptance message and said first signaling message are both formed  
3 according to a common format, wherein said common format contains a field which  
4 indicates whether a message comprises said acceptance message or said first signaling  
5 message.

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

1 Claim 70 (Original): The computer readable medium of claim 69, wherein said  
2 format allows a range of virtual circuits to be specified, said format further allowing a  
3 plurality of traffic parameters to be specified for all of said range of virtual circuits,  
4 wherein said plurality of parameters in said first signaling message specify the desired  
5 parameters and said plurality of parameters in said acceptance message specify the  
6 accepted parameters.

1 Claim 71 (Original): The computer readable medium of claim 70, further  
2 comprising sending a release message requesting release of another range of virtual  
3 circuits.

1 Claim 72 (Currently Amended): A computer readable medium carrying one or more  
2 sequences of instructions for causing a device to support the setting up of a plurality of  
3 virtual circuits between a first end system and a second end system, said plurality of virtual  
4 circuits being set up on a network connecting said first end system to said second end  
5 system, each of said plurality of virtual circuits terminating at said first end system and  
6 said second end system, wherein execution of said one or more sequences of instructions  
7 by one or more processors contained in said device causes said one or more processors to  
8 perform the action of:

9 receiving from said first end system a first signaling request requesting said  
10 plurality of virtual circuits to be set up;

11 provisioning fewer than said plurality of virtual circuits to said second end system;  
12 sending an acceptance message after said provisioning if said plurality of virtual  
13 circuits can be set up between said device and said second end system in response to said  
14 first signaling request alone.

1 Claims 73 - 75 (Canceled)

1 Claim 76 (Currently Amended): The computer readable medium of claim 72-75,  
2 further comprising:

Reply to Advisory Action of May 12, 2006  
Amendment Dated: May 19, 2006

Appl. No.: 09/976,004  
Attorney Docket No.: CSCO-010/4390

3 receiving a second signaling message requesting activation of at least one of said  
4 not-yet-provisioned virtual circuits comprised in said plurality of virtual circuits;  
5 completing provisioning of said at least one of said not-yet-provisioned virtual  
6 circuits; and  
7 sending a completion message indicating said at least one of said not-yet-  
8 provisioned virtual circuits have been activated.

1 Claim 77 (Original): The computer readable medium of claim 76, wherein said first  
2 signaling message contains a plurality of parameters related to a range of virtual circuits  
3 comprised in said plurality of virtual circuits, further comprising:  
4 storing said plurality of parameters associated with said range of virtual circuits;  
5 and  
6 provisioning said range of virtual circuits using said plurality of parameters,  
7 whereby said plurality of parameters are transmitted only once for provisioning said  
8 range of virtual circuits.

1 Claim 78 (Original): The method of claim 1, wherein each of said plurality of  
2 virtual circuits comprises a asynchronous transfer mode (ATM) virtual circuit provided  
between said first end system and said second end system.